



MAGNETIC TIPS

PREPARATION FOR INSTALLATION

The vehicle surface and the dark magnetic side of the sign should be clean, dry and waxed prior to applying.

INSTALLATION

Make contact of one edge of the sign to the vehicle surface in the desired location, let the adjacent part of the sign contact the vehicle surface until the entire sign is held magnetically to the vehicle. If the sign is not in the desired position, remove sign & repeat above. ***(Do not try to straighten the sign by pulling when it is held magnetically to the vehicle. It may stretch the material, especially when hot)***. Avoid placing your sign over chrome trim or surface protrusions of any kind.

CAUTION

Magnetic vehicle signs ***will NOT adhere*** to areas on your car ***where body fillers have been used***. Use caution in applying vehicle signs to areas of your car that have been damaged & repaired in order to avoid losing your signs. Make sure the entire magnet is against the metal surface, in other words, with no air pockets.

CLEANING

Clean your sign with water, a mild detergent, and a soft cloth. Do not leave your magnets on the vehicle when going through a car wash.

WARNING

Trapped moisture, dirt or chemicals may harm your vehicle's finish. To protect the new, clear coat/base coat and vinyl surfaces present on some new vehicles, it is recommended the signs be removed daily and both the signs and the vehicle be cleaned and dried. Pay close attention, especially for the 1st 90 days of use for any changes in your vehicles finish. A generous waxing of both the surface where the signs will be placed and the back of the sign itself will help prevent damage.

STORAGE

To avoid cracking or breaking, do not fold or crease. ***Storing your magnetic sign flat is recommended***. If stored in roll form, roll must be a minimum of 3" in diameter and lettering on the outside of roll to prevent wrinkles. Do not store faces against each other or they will de-polarize.